

| | | | | |
|----------------------------------|-------|--------|----------|------------|
| Name: | Lfd.: | Page: | Version: | Date: |
| Aloxan [®] Silver-Spray | 1 | 1 of 1 | 2 | 02/07/2013 |

| | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Product name: | |
| Aloxan [®] Silver-Spray | |
| Product type: | |
| Animal care/cosmetic product | |
| Description: | |
| Film-forming aluminium micronized spray for the protection of the sensitive animal skin against dirt or other environmental factors. | |
| Fields of application: | |
| Aloxan [®] Silver-Spray forms a close and anti-humidity metal film, that keeps elastic and breathable. | |
| Ingredients | |
| Aluminium powder, Solvents, Propane-butane propellant gas mix | |
| Instructions for use: | |
| Shake well before use, until the inside steel ball has completely twirled the components. Spray from a distance of 10-20 cm on the clean and dry area, until a fine metal protective film is visible. | |
| Target species: | |
| Bovine, Porcine, Equine, Ovine, Caprine, Feline, Canine and Exotic Species | |
| Hazards: | |
| Classification in accordance with Directive 67/548/EEC or 1999/45/EC: Extremely flammable, Irritant, F+; Xi; R12; R36; R67; R66 Please note the safety data sheet! | |
| Chemical and physical parameters: | |
| Form: | Aerosol |
| Odour: | Solvent-like |
| Colour: | Silver |
| Density: | 0,67 g/cm ³ |
| VOC: | 92,6 % |
| Sales unit(s): | |
| 200ml aerosol can | SA00090 |
| Packaging: | |
| Pressure container made of coated tinplate with a valve mechanism and spray nozzle made of plastic materials (aerosol can, DIN EN 10202:2001, DIN EN 15007). 12 x 200 ml aerosol cans in a cardboard box (218 x 164 x178 mm). | |
| Storage conditions: | |
| Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Recommended storage temperature: 10-25°C. No liability in case of improper handling or storage. | |
| Shelf life: | |
| 60 months from date of production | |
| Country of Origin: | |
| Germany | |
| Subject to modifications! | |